



CORPORATE WOOD

An umbrella designed and manufactured for its strength and durability yet at a price to suit the corporate market. With colour coded Nylon hubs, a wooden frame and the canvas printed to the client's requirements. Canvas colours available from the Cedarbrook and Sunbrella Range.

OPTIONS

SHAPE & SIZE



Square
4 strut in:

2.0 meter
2.5 meter

OR



Hexagonal
6 strut in:

2.6 meter
3.0 meter




Strut configuration:

Four (square) or Six (hexagonal) wooden struts, Karrigum/Saligna plantation grown hardwood with FSC grading wooden struts coated with a clear UV lacquer.



Height:

2,05m at rim. Provides more shade and no head bumping for taller people.



Hubs & Pole:

Nylon UV treated hubs and a 48mm diameter Karrigum/Saligna pole with a galvanised mild steel sleeve for protection.



Opening Mechanism:

Single pulley and rope opening mechanism with attached stainless steel holding pin.



Joints / Fittings:

Nylock nut & bolt set on wooden frame.



pulley



UV TREATED
NYLON HUB



OPENING
MECHANISM



SEAMLESS
POPRIVETTS



BRANDING





CORPORATE ALUMINIUM

An umbrella designed and manufactured for its strength and durability yet at a price to suit the corporate market. With colour coded Nylon hubs, an aluminium frame and the canvas printed to the client's requirements. Canvas colours available from the Cedarbrook and Sunbrella Range.

OPTIONS

SHAPE & SIZE



Square
4 strut in:
2.0 meter
2.5 meter

OR



Hexagonal
6 strut in:
2.6 meter
3.0 meter




Strut configuration:

Four (square) or Six (hexagonal) aluminium struts with a wall thickness of 1.5mm.



Height:

2,05m at rim. Provides more shade and no head bumping for taller people.



Hubs & Pole:

Nylon UV treated hubs and a aluminium pole with a diameter of 48mm, Wall thickness of 1mm and anodised to 25mic. Also with a bottom aluminium sleeve for protection.



Opening Mechanism:

Single pulley and rope opening mechanism with attached stainless steel holding pin.



Joints / Fittings:

Poprivetts on aluminium frame.



pulley



UV TREATED
NYLON HUB



OPENING
MECHANISM



NYLON
BRACKETS



BRANDING

